

View Online at <https://aerobasegroup.com/nsn/6625-00-061-3904>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

2.285 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.281 inches

**Overall Height:**

4.000 inches

**Overall Width:**

4.250 inches

**Scale Division Quantity:**

50 single indicator 2nd range

**Mounting Stud Length:**

0.500 inches

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant

**Furnished Items And Quantity:**

Nut 7; washer 7

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

0.937 inches

**Meter Body Diameter Behind Mounting Flange:**

3.250 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0 to 500.0 volts, dc single indicator 2nd range

**Mounting Stud Diameter:**

0.151 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

3 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0