NSN 6625-00-063-0687

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-063-0687

| Circuit Current For Which Designed: |
|---|
| Ac |
| Overall Length: |
| 2.220 inches |
| Mounting Hole Diameter: |
| 0.156 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Overall Diameter: |
| 3.510 inches |
| Environmental Protection: |
| Dust resistant |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.590 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.760 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |

NSN 6625-00-063-0687

Voltmeter - Page 2 of 2



| Measurement Range: |
|---|
| +0.0 to 500.0 volts, ac single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| No |
| Fiig: |

A310a0