NSN 6625-00-065-3266

Ammeter - Page 1 of 2

Dc

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-065-3266

Mounting Hole Diameter:					
0.125 inches					
Scale Division Quantity:					
10 single indicator single range					
Overall Diameter:					
2.695 inches					
Mounting Bolt Circle Diameter:					
2.440 inches					
Installation Design:					
Panel					
Mounting Arrangement Style:					
Three hole/stud bolt circle					
Sensitivity Rating:					
50.0 millivolts					
Dial Scale Marking Color:					
Black single indicator single range					
Accuracy In Percent:					
-2.0 to 2.0 at full scale single indicator single range					
Meter Depth Behind Mounting Flange:					
1.438 inches					
Meter Body Diameter Behind Mounting Flange:					
g.					
2.210 inches					
2.210 inches					
2.210 inches Movement Type:					
2.210 inches Movement Type: Moving coil, permanent magnet					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color:					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity:					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided:					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided: Magnetic shield					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method:					
2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method: Jewel pivot base					
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:					
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug					
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug Special Markings:					
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 500.0 milliamperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug Special Markings: Milliamperes dc					

NSN 6625-00-065-3266

Ammeter - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0