

View Online at <https://aerobasegroup.com/nsn/6625-00-065-5258>

Circuit Current For Which Designed:

Ac

Overall Length:

2.315 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

5 single indicator single range

Overall Diameter:

2.695 inches

Environmental Protection:

Dust resistant and humidity resistant and vibration resistant and watertight

Mounting Bolt Circle Diameter:

2.440 inches

End Application:

485I tacs, aircraft support equipment a-10, ov-10a

Furnished Items And Quantity:

Term. Hdw 2; mtg hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.190 inches

Meter Body Diameter Behind Mounting Flange:

2.060 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Percent load current at 0.8pf; 0, 25, 50, 75, 100, 125

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Magnetic shield and rectifier circuit and zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Weapon system essential

Special Markings:

Red band from 100 to 125; line at 80 pct reads 100 % (1.0 pf)

Material:

Steel

Surface Treatment:

Cadmium

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0