

View Online at <https://aerobasegroup.com/nsn/6625-00-065-5258>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.315 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

5 single indicator single range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Dust resistant and humidity resistant and vibration resistant and watertight

**Mounting Bolt Circle Diameter:**

2.440 inches

**End Application:**

485I tacs, aircraft support equipment a-10, ov-10a

**Furnished Items And Quantity:**

Term. Hdw 2; mtg hdw 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.190 inches

**Meter Body Diameter Behind Mounting Flange:**

2.060 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Percent load current at 0.8pf; 0, 25, 50, 75, 100, 125

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Magnetic shield and rectifier circuit and zero adjuster

**Criticality Code Justification:**

Feat

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Weapon system essential

**Special Markings:**

Red band from 100 to 125; line at 80 pct reads 100 % (1.0 pf)

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0