NSN 6625-00-065-6198

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-065-6198

Circuit Current For Which Designed:
Dc
Overall Length:
1.600 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.093 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.285 inches
Overall Height:
0.965 inches
Overall Width:
2.260 inches
Mounting Hole Diameter:
0.138 inches
Scale Division Quantity:
20 single indicator single range
Environmental Protection:
Dustproof
Indicator Type:
Dial w/pointer
Installation Design:
Installation Design: Panel
Panel
Panel Mounting Arrangement Style:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range Movement Type:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range Movement Type: Moving coil, permanent magnet
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range Movement Type: Moving coil, permanent magnet Background Color:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 1200.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0 to 3.0 at full scale single indicator single range Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Power Source:

Linear single indicator single range

Scale Graduation Type:

NSN 6625-00-065-6198

Ammeter - Page 2 of 2



Measurement Range:
-100.0/+100.0 microamperes, dc single indicator single range
Circuit Construction Type:
Nonelectronic
Scale Selection Method:
Switch
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular surface mtg
Fsc Application Data:
Test set electronic
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0