

View Online at <https://aerobasegroup.com/nsn/6625-00-068-0607>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.785 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

50 single indicator single range

Overall Diameter:

3.491 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

3.125 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3; shunt, wire 1; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

5.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.430 inches

Meter Body Diameter Behind Mounting Flange:

2.669 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 100.0 millivolts, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 connector, receptacle

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0