## NSN 6625-00-068-1744

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-068-1744

Circuit Current For Which Designed:
Dc
Overall Length:
1.990 inches
Overall Height:
2.730 inches
Overall Width:
2.730 inches
Scale Division Quantity:
30 single indicator single range
Mounting Stud Length:
0.460 inches
Environmental Protection:
Dustproof
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Mtg hardware included
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Manus Commander of Otales
Mounting Arrangement Style:
Three hole/stud bolt circle
Three hole/stud bolt circle
Three hole/stud bolt circle Sensitivity Rating:
Three hole/stud bolt circle  Sensitivity Rating:  50.0 millivolts
Three hole/stud bolt circle  Sensitivity Rating:  50.0 millivolts  Dial Scale Marking Color:
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches  Meter Body Diameter Behind Mounting Flange:
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches  Meter Body Diameter Behind Mounting Flange: 2.220 inches
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches  Meter Body Diameter Behind Mounting Flange: 2.220 inches  Movement Type:
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches  Meter Body Diameter Behind Mounting Flange: 2.220 inches  Movement Type:  Moving coil, permanent magnet
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches  Meter Body Diameter Behind Mounting Flange: 2.220 inches  Movement Type:  Moving coil, permanent magnet  Background Color:
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches  Meter Body Diameter Behind Mounting Flange: 2.220 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range
Three hole/stud bolt circle  Sensitivity Rating: 50.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.510 inches  Meter Body Diameter Behind Mounting Flange: 2.220 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Pointer Color:

## NSN 6625-00-068-1744

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+3.0 milliamperes, dc single indicator single range
Circuit Construction Type:
Nonelectronic
Mounting Stud Diameter:
0.112 inches
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Fan shape flush mtg
Fsc Application Data:
Test set electronic
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0