

View Online at <https://aerobasegroup.com/nsn/6625-00-068-3517>

Circuit Current For Which Designed:

Dc

Overall Length:

1.943 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

10 single indicator single range

Overall Diameter:

3.500 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.063 inches

Meter Body Diameter Behind Mounting Flange:

2.675 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 150.0 volts, dc single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Plus and minus signs over positive and negative terminals respectively

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Drawing and parts iaw mil-std-130

Style Designator:

Round flush mtg

Supplementary Features:

Term. Res 1000 ohms

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0