NSN 6625-00-069-0685

Ammeter - Page 1 of 2

Dc

Overall Length: 1.500 inches

0.125 inches

2.690 inches

Mounting Hole Diameter:

Scale Division Quantity: 50 single indicator single range

Environmental Protection:

Overall Diameter:

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-069-0685

| Shock resistant and vibration resistant |
|---|
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 75.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Unable To Decode: |
| Magnetic or unable to decode |
| Meter Depth Behind Mounting Flange: |
| 1.062 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.150 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |

NSN 6625-00-069-0685

Ammeter - Page 2 of 2



| Measurement Range: |
|--|
| +0.0/+5.0 amperes, $$ dc single indicator single range |
| Circuit Construction Type: |
| Nonelectronic |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Ruggedized |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |