## NSN 6625-00-069-5474

Ammeter - Page 1 of 2

**Mounting Hole Diameter:** 

**Scale Division Quantity:** 

0.156 inches

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-069-5474

Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 5.0 ohms per volt Dial Scale Marking Color: Black single indicator all ranges Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all rang Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flange: 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug	
Mounting Bolt Circle Diameter: 3.156 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 5.0 ohms per volt Dial Scale Marking Color: Black single indicator all ranges Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all rang Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flant 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st rates Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 5.0 ohms per volt Dial Scale Marking Color: Black single indicator all ranges Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all rang Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flange: 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 5.0 ohms per volt Dial Scale Marking Color: Black single indicator all ranges Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all rang Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flant 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st rang Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating: 5.0 ohms per volt  Dial Scale Marking Color: Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all range  Meter Depth Behind Mounting Flange: 1.438 inches  Meter Body Diameter Behind Mounting Flange: 1.672 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method: Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method: Jewel pivot base  Circuit Attachment Method And Quantity:	
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 5.0 ohms per volt Dial Scale Marking Color: Black single indicator all ranges Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all range Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flange: 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st rascale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Three hole/stud bolt circle  Sensitivity Rating: 5.0 ohms per volt  Dial Scale Marking Color: Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all rang  Meter Depth Behind Mounting Flange: 1.438 inches  Meter Body Diameter Behind Mounting Flan 2.672 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ra  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
Sensitivity Rating: 5.0 ohms per volt  Dial Scale Marking Color: Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all range Meter Depth Behind Mounting Flange: 1.438 inches  Meter Body Diameter Behind Mounting Flange: 2.672 inches  Movement Type: Moving coil, permanent magnet  Background Color: White single indicator all ranges  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method: Switch  Features Provided: Magnetic shield and portable  Movement Suspension Method: Jewel pivot base  Circuit Attachment Method And Quantity:	
Dial Scale Marking Color: Black single indicator all ranges Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all range Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flange: 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Dial Scale Marking Color: Black single indicator all ranges Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all range Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flange: 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Black single indicator all ranges  Accuracy In Percent:  -2.0 to 2.0 at full scale single indicator all range  Meter Depth Behind Mounting Flange:  1.438 inches  Meter Body Diameter Behind Mounting Flange:  2.672 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
Accuracy In Percent:  -2.0 to 2.0 at full scale single indicator all range Meter Depth Behind Mounting Flange:  1.438 inches Meter Body Diameter Behind Mounting Flange: 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
-2.0 to 2.0 at full scale single indicator all rang Meter Depth Behind Mounting Flange: 1.438 inches Meter Body Diameter Behind Mounting Flant 2.672 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Meter Depth Behind Mounting Flange:  1.438 inches  Meter Body Diameter Behind Mounting Flant 2.672 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
1.438 inches  Meter Body Diameter Behind Mounting Flat 2.672 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ra  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	es
Meter Body Diameter Behind Mounting Flat 2.672 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
2.672 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	nge:
Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ranges  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
Background Color: White single indicator all ranges Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st range: Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
White single indicator all ranges  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st range: Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st range: Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
3 unthreaded hole  Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ra  Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Measurement Range: +0.0 to 1.0 amperes, dc single indicator 1st ra Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
+0.0 to 1.0 amperes, dc single indicator 1st ra  Scale Selection Method:  Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
Scale Selection Method: Switch Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Switch  Features Provided:  Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	inge
Features Provided: Magnetic shield and portable Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:	
Magnetic shield and portable  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:	
Jewel pivot base  Circuit Attachment Method And Quantity:	
Circuit Attachment Method And Quantity:	
2 solder lug	
Style Designator:	
Round flush mtg	

## NSN 6625-00-069-5474

Ammeter - Page 2 of 2



	<b>L</b> -	11		ife	_
3	ne	п	_	пe	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0