

View Online at <https://aerobasegroup.com/nsn/6625-00-070-1601>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.480 inches

**Mounting Hole Diameter:**

Between 0.143 inches and 0.157 inches

**Scale Division Quantity:**

90 single indicator single range

**Overall Diameter:**

3.510 inches

**Environmental Protection:**

Humidity resistant and shock resistant and watertight

**Mounting Bolt Circle Diameter:**

Between 3.155 inches and 3.165 inches

**Furnished Items And Quantity:**

Nut 3; washer 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

110.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Panel For Which Designed:**

Nonmagnetic

**Meter Depth Behind Mounting Flange:**

1.660 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

110, 100, 50, 0, 50, 100, 110, percent

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Special Features:**

Ruggedized

**Special Markings:**

Percent

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-10304

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0