

View Online at <https://aerobasegroup.com/nsn/6625-00-070-5779>

Circuit Current For Which Designed:

Ac

Overall Length:

1.950 inches

Mounting Hole Diameter:

Between 0.140 inches and 0.150 inches

Scale Division Quantity:

45 single indicator single range

Overall Diameter:

4.560 inches

Mounting Bolt Circle Diameter:

4.120 inches

Furnished Items And Quantity:

Screws 6; lock washers 6; hex nuts 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator single range

Panel For Which Designed:

Magnetic

Meter Depth Behind Mounting Flange:

1.500 inches

Meter Body Diameter Behind Mounting Flange:

3.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

6 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 45.0 microamperes, ac single indicator single range

Scale Selection Method:

Terminal

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

4 solder lug

Special Features:

Ruggedized

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0