

View Online at <https://aerobasegroup.com/nsn/6625-00-073-0048>

Circuit Current For Which Designed:

Ac

Overall Length:

2.799 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.474 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

3.188 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3; seal

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

2

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+58.000 to 62.000 hertz

Dial Scale Marking Color:

White single indicator single range

Resonant Reed Quantity:

5

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.433 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Vibrating reed

Background Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Measurement Range:

+58.0 to 62.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Shatterproof glass

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

Stamp on back, sealed do not open

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0