

View Online at <https://aerobasegroup.com/nsn/6625-00-074-9549>

Circuit Current For Which Designed:

Dc

Overall Length:

1.336 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.074 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.620 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

2 single indicator single range

Overall Diameter:

1.455 inches

Environmental Protection:

Cold resistant and fungus resistant and heat resistant and humidity proof and salt spray resistant and vibration resistant

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 0.956 inches and 1.271 inches

Meter Body Diameter Behind Mounting Flange:

1.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Plus sign; minus sign

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint lusterless

Special Test Features:

Vibration iaw mil-e-5272c; salt spray iaw mil-e-3272b; temperature mil-std-810; conforms to mil-m-17275 type mr050100dcuar

Style Designator:

Round flush mtg

Supplementary Features:

Internal resistance 1200 ohms plus or minus 17 percent

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0