NSN 6625-00-077-3538

Ammeter - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/6625-00-077-3538

| view Offiline at https://derobasegroup.com/nsii/0025-00-077-5550 |
|---|
| Circuit Current For Which Designed: |
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 1500.0 |
| Overall Length: |
| 1.625 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.312 inches |
| Overall Height: |
| 1.750 inches |
| Overall Width: |
| 1.750 inches |
| Mounting Hole Diameter: |
| 0.125 inches |
| Scale Division Quantity: |
| 15 single indicator single range |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Furnished Items And Quantity: |
| Washer 4; nut 4 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 1.0 milliamperes |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Panel For Which Designed: |
| Magnetic or nonmagnetic |
| Meter Depth Behind Mounting Flange: |
| 1.000 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.510 inches |

Movement Type:

Moving coil, permanent magnet

NSN 6625-00-077-3538

Ammeter - Page 2 of 3



| Background Color: |
|---|
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 4 screw and 4 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+30.0 milliamperes, dc single indicator single range |
| Circuit Construction Type: |
| Nonelectronic |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder stud |
| Special Features: |
| Ruggedized |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Enamel |
| Special Test Features: |
| Conforms to mil-m-10304/21 |
| Style Designator: |
| Rectangular flush mtg |
| Supplementary Features: |
| 1 % dc resistance tolerance |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| N/ 1 11/ 12 |

Yes - demil/mli

NSN 6625-00-077-3538

Ammeter - Page 3 of 3



Fiig:

A310a0