

View Online at <https://aerobasegroup.com/nsn/6625-00-078-0382>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

4.152 inches

**Overall Height:**

1.284 inches

**Overall Width:**

4.260 inches

**Mounting Hole Diameter:**

0.149 inches

**Scale Division Quantity:**

50 single indicator single range

**Distance Between Mounting Facility Centers:**

3.780 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

220.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.242 inches

**Meter Body Width Behind Mounting Flange:**

4.180 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+50.0 microamperes, dc single indicator single range

**Circuit Construction Type:**

Nonelectronic

**Meter Body Height Behind Mounting Flange:**

1.160 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**FiiG:**

A310a0