

View Online at <https://aerobasegroup.com/nsn/6625-00-078-6787>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.130 inches

**Scale Division Quantity:**

20 single indicator all ranges

**Mounting Stud Length:**

0.500 inches

**Overall Diameter:**

2.695 inches

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Washers 3, nuts 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

250.0 millivolts

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Panel For Which Designed:**

Magnetic

**Meter Depth Behind Mounting Flange:**

1.500 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0 to 10.0 milliamperes, dc single indicator 2nd range

**Circuit Construction Type:**

Nonelectronic

**Mounting Stud Diameter:**

0.125 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Special Features:**

Ruggedized

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0