

View Online at <https://aerobasegroup.com/nsn/6625-00-079-3676>

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Accessory Components And Quantity:**

Adapter 2, cable assembly 1, cord, power 1, filter, light 1, lead, ground 1, lead, test 1, probe, test 1, tip, test 1

**Voltage Rating:**

Between 105.0 volts and 125.0 volts

**Beam Quantity:**

1

**Accuracy Range In Percent:**

+0.0 to 3.0

**Screen Size:**

5 in.

**Expanded Sweep:**

Provided

**Amplifier Deflection Sensitivity Provision:**

Not provided

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 0.0 megahertz and 15.0 megahertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Amplitude Calibrating Voltage Waveform:**

Square wave

**Calibrating Peak To Peak Amplitude:**

1.0 volts

**Measurement Range Quantity:**

3

**Measurement Range Steps:**

0.05 to 20 v per cm

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Fsc Application Data:**

1. Oscilloscope, except, specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T320-g