

View Online at <https://aerobasegroup.com/nsn/6625-00-079-3676>

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Accessory Components And Quantity:

Adapter 2, cable assembly 1, cord, power 1, filter, light 1, lead, ground 1, lead, test 1, probe, test 1, tip, test 1

Voltage Rating:

Between 105.0 volts and 125.0 volts

Beam Quantity:

1

Accuracy Range In Percent:

+0.0 to 3.0

Screen Size:

5 in.

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 megahertz and 15.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

1.0 volts

Measurement Range Quantity:

3

Measurement Range Steps:

0.05 to 20 v per cm

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Fsc Application Data:

1. Oscilloscope, except, specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g