

View Online at <https://aerobasegroup.com/nsn/6625-00-079-5247>

Circuit Current For Which Designed:

Dc

Overall Length:

1.550 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.978 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.536 inches

Overall Height:

4.070 inches

Overall Width:

4.530 inches

Scale Division Quantity:

100 single indicator single range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Nut 6; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

85.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Panel For Which Designed:

Unable to decode or nonmagnetic

Meter Depth Behind Mounting Flange:

1.150 inches

Meter Body Diameter Behind Mounting Flange:

2.760 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-500.0/+500.0 microamperes, dc single indicator single range

Circuit Construction Type:

Nonelectronic

Mounting Stud Diameter:

0.138 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0