

View Online at <https://aerobasegroup.com/nsn/6625-00-080-0070>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

6.690 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.375 inches

Overall Height:

6.880 inches

Overall Width:

6.630 inches

Scale Division Quantity:

30 single indicator all ranges

Mounting Stud Length:

0.530 inches

Furnished Items And Quantity:

Five foot shunt leads 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Panel For Which Designed:

Nonmagnetic

Meter Depth Behind Mounting Flange:

5.520 inches

Meter Body Width Behind Mounting Flange:

5.670 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 600.0 amperes, dc single indicator 3rd range

Mounting Stud Diameter:

0.164 inches

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

5.920 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular semi-flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0