NSN 6625-00-080-2096

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-080-2096

Circuit Current For Which Designed:
Dc
Overall Length:
2.650 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
60 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 7; lockwasher 5; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
150.0 millivolts
Dial Scale Marking Color:
Green, phosphorescent single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
Black single indicator single range

Green, phosphorescent single indicator single range

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Pointer Color:

Linear single indicator single range

NSN 6625-00-080-2096

Ammeter - Page 2 of 2



Measurement Range:
+0.0/+300.0 milliamperes, dc single indicator single range
Features Provided:
Self-illumination facility
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Material:
Plastic and steel
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-prf-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-10304/5 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A310a0
Mil-std (military Standard):
Mil-prf-10304 spec.