NSN 6625-00-080-4276

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-080-4276

| AC |
|---|
| Mounting Hole Diameter: |
| 0.156 inches |
| Overall Diameter: |
| 3.438 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Furnished Items And Quantity: |
| Current transformer 1 |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.0/+1.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.625 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.750 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Measurement Range: |
| +0.0/+500.0 amperes, ac single indicator 3rd range |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Ac also designed for nonmagnetic panel |
| Style Designator: |
| Round flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 6625-00-080-4276

Ammeter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A310a0