

View Online at <https://aerobasegroup.com/nsn/6625-00-081-0126>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

11.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.376 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.376 inches

**Overall Height:**

Between 4.250 inches and 4.750 inches

**Overall Width:**

Between 4.250 inches and 4.750 inches

**Scale Division Quantity:**

30 single indicator single range

**Frequency Rating:**

60.0 hertz

**Mounting Stud Length:**

0.625 inches

**Environmental Protection:**

Dust resistant and humidity resistant and shock resistant and vibration resistant

**Furnished Items And Quantity:**

Mtg hdw 4; term. Hdw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

10.0 volt-amperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

9.000 inches

**Meter Body Diameter Behind Mounting Flange:**

3.980 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 300.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Electrical overload protection and magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Phase:**

Single

**Special Features:**

Ruggedized

**Material:**

Plastic or stainless steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Resists friction effects

**Test Data Document:**

81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-m-16034/3 government specification

**Fsc Application Data:**

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0