

View Online at <https://aerobasegroup.com/nsn/6625-00-086-9353>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

5000.0

Overall Length:

2.590 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.040 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.670 inches

Overall Height:

3.940 inches

Overall Width:

4.250 inches

Scale Division Quantity:

50 single indicator 2nd range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Nut 14; washer 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Red single indicator 1st range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.120 inches

Meter Body Diameter Behind Mounting Flange:

3.250 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

1 flange and 4 threaded stud

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

+0.0 to 20.0 decibels single indicator 1st range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Knife edge pointer and magnetic shield

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Rms milli-volts written in black above the scale, db attenuation written in red below the scale

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Steel panel mounting 0.120 in. Thick to assure proper adjustment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0