## NSN 6625-00-086-9353

Multiple Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-086-9353

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
5000.0
Overall Length:
2.590 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.040 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.670 inches
Overall Height:
3.940 inches
Overall Width:
4.250 inches
Scale Division Quantity:
50 single indicator 2nd range
Mounting Stud Length:
0.500 inches
Furnished Items And Quantity:
Nut 14; washer 8
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Red single indicator 1st range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.120 inches
Meter Body Diameter Behind Mounting Flange:
3.250 inches
Movement Type:
Moving coil, permanent magnet
Background Color:

White single indicator all ranges

## **NSN 6625-00-086-9353**Multiple Scale Meter - Page 2 of 2



Pointer Color:
Black single indicator all ranges
Mounting Facility Type And Quantity:
1 flange and 4 threaded stud
Scale Graduation Type:
Nonlinear single indicator 1st range
Measurement Range:
+0.0 to 20.0 decibels single indicator 1st range
Mounting Stud Diameter:
0.138 inches
Features Provided:
Knife edge pointer and magnetic shield
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Rms milli-volts written in black above the scale, db attenuation written in red below the scale
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Supplementary Features:
Steel panel mounting 0.120 in. Thick to assure proper adjustment
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A310a0