## NSN 6625-00-087-2143

Multiple Scale Meter - Page 1 of 2

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-087-2143

Overall Length:
2.443 inches
Overall Height:
4.727 inches
Overall Width:
5.852 inches
Scale Division Quantity:
64 single indicator 3rd range
Mounting Stud Length:
0.603 inches
Distance Between Mounting Facility Centers:
4.500 inches
Furnished Items And Quantity:
Term hdw 2; mtg hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Two hole/stud
Dial Scale Marking Color:
Diai Scale Marking Soloi.
Black single indicator all ranges
_
Black single indicator all ranges
Black single indicator all ranges  Accuracy In Percent:
Black single indicator all ranges  Accuracy In Percent:  -2.0 to 2.0 at full scale single indicator all ranges
Black single indicator all ranges  Accuracy In Percent:  -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange:
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange:
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:  Moving coil, permanent magnet
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:  Moving coil, permanent magnet  Background Color:
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Pointer Color:
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Pointer Color:  Red single indicator all ranges
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Pointer Color:  Red single indicator all ranges  Power Source:
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type: Moving coil, permanent magnet  Background Color: White single indicator all ranges  Pointer Color: Red single indicator all ranges  Power Source: External
Black single indicator all ranges  Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges  Meter Depth Behind Mounting Flange: 1.105 inches  Meter Body Diameter Behind Mounting Flange: 2.725 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator all ranges  Pointer Color:  Red single indicator all ranges  Power Source:  External  Mounting Facility Type And Quantity:

## NSN 6625-00-087-2143

Multiple Scale Meter - Page 2 of 2



Measurement Range:
-10.0 to 2.0 decibels above or below one milliwatt single indicator 1st range
Mounting Stud Diameter:
0.138 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
600 ohms res
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A310a0