

View Online at <https://aerobasegroup.com/nsn/6625-00-087-6319>

**Width:**

35.000 inches

**Length:**

35.000 inches

**Ac Voltage Rating:**

Between 108.0 volts and 121.0 volts

**Dc Voltage Rating:**

Between 21.5 volts and 29.0 volts

**Frequency Rating:**

Between 300.0 hertz and 420.0 hertz

**Major Components:**

Junction box; vibration isolator; control indicator; cable

**Accessory Component Quantity:**

1 and 1 and 1 and 11

**Accessory Controlling Agency:**

Sperry gyroscope co

**Accessory Identifying Number:**

1509963 part no. And 334286 part no. And 1510030 part no. And 1510031 part no. And 1510032 part no. And 1510033 part no. And 1510034 part no. And 1510035 part no. And 1510036 part no. And 1510037 part no. And 1510038 part no. And 1510039 part no. And 1510040 part no.

**Internal Battery Accommodation:**

Not included

**Material And Location:**

Aluminum carrying case

**Inclosure Feature:**

Multiple item w/carrying case

**Test Type For Which Designed:**

Servo dynamic test, signal simulation and generation of amp checkout and alignment

**Operating Test Capability:**

Input signals, 4.3 kmc porm 5 kmc, 380 to 420 cycles and dc, 455 kc, 395 kc, 30 kc, 60 kc and 300 cycles, servo dynamic test signal, 400 cycles by 0.015 cycles, 455 kc linear wideband amplifier and detector, o/a gain, 54 db porm 1 db

**Phase:**

Single

**Functional Classification:**

Aa-9.3

**Height:**

37.000 inches

**Fsc Application Data:**

1. Test set, radar, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T228-a