NSN 6625-00-087-7266

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-087-7266

Circuit Current For Which Designed: Ac Dielectric Withstanding Voltage In Volts: 3000.0

Overall Length:

2.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.856 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.856 inches

Overall Height:

2.375 inches

Overall Width:

2.375 inches

Mounting Hole Diameter:

0.170 inches

Scale Division Quantity:

50 single indicator single range

Frequency Rating:

60.0 hertz

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 8; lockwasher 6; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Unable To Decode:

Magnetic or unable to decode

Meter Depth Behind Mounting Flange:

1.375 inches

Meter Body Diameter Behind Mounting Flange:

2.060 inches

NSN 6625-00-087-7266

Ammeter - Page 2 of 2



Movement Type: Moving coil, permanent magnet **Background Color:** White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 screw and 4 unthreaded hole Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0 to 100.0 amperes, ac single indicator single range **Features Provided:** Magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solder lug and 2 threaded stud **Special Features:** Ruggedized **Special Markings:** On back, sealed do not open Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Cadmium and chromate and enamel semigloss **Style Designator:** Rectangular flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A310a0