

View Online at <https://aerobasegroup.com/nsn/6625-00-088-6650>

Circuit Current For Which Designed:

Ac

Overall Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

4.156 inches

Overall Width:

6.656 inches

Mounting Hole Diameter:

0.138 inches

Scale Division Quantity:

60 single indicator 8th range

Frequency Rating:

Between 50.000 hertz and 60.000 hertz

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

3.750 inches

Meter Body Width Behind Mounting Flange:

5.700 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 300.0 volts, ac single indicator 8th range

Scale Selection Method:

Switch

Meter Body Height Behind Mounting Flange:

3.780 inches

Circuit Attachment Method And Quantity:

2 solder lug

Operating Voltage Rating In Volts:

Between 105.0 ac and 125.0 ac

Phase:

Single

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0