

View Online at <https://aerobasegroup.com/nsn/6625-00-088-6650>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches

**Overall Height:**

4.156 inches

**Overall Width:**

6.656 inches

**Mounting Hole Diameter:**

0.138 inches

**Scale Division Quantity:**

60 single indicator 8th range

**Frequency Rating:**

Between 50.000 hertz and 60.000 hertz

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

3.750 inches

**Meter Body Width Behind Mounting Flange:**

5.700 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0 to 300.0 volts, ac single indicator 8th range

**Scale Selection Method:**

Switch

**Meter Body Height Behind Mounting Flange:**

3.780 inches

**Circuit Attachment Method And Quantity:**

2 solder lug

**Operating Voltage Rating In Volts:**

Between 105.0 ac and 125.0 ac

**Phase:**

Single

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0