NSN 6625-00-089-6749

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-089-6749

Circuit Current For Which Designed:
Dc
Overall Length:
1.475 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.880 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches
Overall Height:
3.750 inches
Overall Width:
3.370 inches
Scale Division Quantity:
50 single indicator single range
Mounting Stud Length:
0.375 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Mounting Arrangement Style: Four hole/stud rectangular/square
Four hole/stud rectangular/square
Four hole/stud rectangular/square Sensitivity Rating:
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color:
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed:
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic Meter Depth Behind Mounting Flange:
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic Meter Depth Behind Mounting Flange: 0.850 inches
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic Meter Depth Behind Mounting Flange: 0.850 inches Meter Body Diameter Behind Mounting Flange:
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic Meter Depth Behind Mounting Flange: 0.850 inches Meter Body Diameter Behind Mounting Flange: 2.680 inches
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic Meter Depth Behind Mounting Flange: 0.850 inches Meter Body Diameter Behind Mounting Flange: 2.680 inches Movement Type:
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic Meter Depth Behind Mounting Flange: 0.850 inches Meter Body Diameter Behind Mounting Flange: 2.680 inches Movement Type: Moving coil, permanent magnet
Four hole/stud rectangular/square Sensitivity Rating: 10.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Panel For Which Designed: Magnetic Meter Depth Behind Mounting Flange: 0.850 inches Meter Body Diameter Behind Mounting Flange: 2.680 inches Movement Type: Moving coil, permanent magnet Background Color:

4 threaded stud

Mounting Facility Type And Quantity:

NSN 6625-00-089-6749

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0 to 10.0 amperes, dc single indicator single range
Circuit Construction Type:
Nonelectronic
Mounting Stud Diameter:
0.138 inches
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set electronic
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0