

View Online at <https://aerobasegroup.com/nsn/6625-00-093-0672>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

2.646 inches

Overall Height:

0.765 inches

Overall Width:

1.865 inches

Scale Division Quantity:

10 single indicator all ranges

Frequency Rating:

60.0 hertz

Environmental Protection:

Shock resistant

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.795 inches

Meter Body Width Behind Mounting Flange:

1.600 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 screw and 1 bracket

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 50.0 volts single indicator 3rd range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

0.515 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug or 2 solder stud

Phase:

Single

Special Features:

Used w/external multiplier

Special Markings:

A for 0 to 10 scale; b for 0 to 20; c for 0 to 50

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

27.5 ohms internal resistance

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0