NSN 6625-00-093-6739

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-093-6739

Mounting Type:
Portable case
Overall Length:
12.000 inches
Overall Width:
15.000 inches
Current Type:
Ac
Frequency Rating:
60.0 hertz
Case Material:
Aluminum
Case Surface Treatment:
Enameled
Frequency Range Rating:
+0.030 to 9.960 kilohertz
Accessory Component Quantity:
1 and 1 and 1
End Application:
Type no. Md-83/arn
Accessory Controlling Agency
Accessory Controlling Agency:
Jcens
Jcens
Jcens Accessory Identifying Number:
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no.
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation:
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating:
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating:
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type:
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type: Fm
Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type: Fm Accessory Component Name:
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type: Fm Accessory Component Name: Cord; cord; case
Jcens Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type: Fm Accessory Component Name: Cord; cord; case Fixed Frequency Quantity:
Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type: Fm Accessory Component Name: Cord; cord; case Fixed Frequency Quantity: 5
Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type: Fm Accessory Component Name: Cord; cord; case Fixed Frequency Quantity: 5 Crystal Controlled Feature:
Accessory Identifying Number: Cg530/u type no. And cx-237/u type no. And cf-663/arn type no. Internal Battery Accommodation: Not included Output Impedance Rating: 500.0 ohms Voltage Rating: 115.0 volts Modulation Type: Fm Accessory Component Name: Cord; cord; case Fixed Frequency Quantity: 5 Crystal Controlled Feature: Not provided

Signal Output Constancy:

Porm 2 pct db maximum variation throughout frequency range

NSN 6625-00-093-6739 Signal Generator - Page 2 of 2



Modulator Location:
Internal
Modulated Frequency Rating:
30.0 hertz and 90.0 hertz and 150.0 hertz and 1.0 kilohertz and 9.96 kilohertz
Modulation Degree:
16.0 deviation
Phase:
Single
Special Features:
12 in. Deep
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T320-j