

View Online at <https://aerobasegroup.com/nsn/6625-00-102-4311>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

3.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.718 inches

Overall Height:

1.000 inches

Overall Width:

2.688 inches

Mounting Hole Diameter:

0.140 inches

Scale Division Quantity:

24 single indicator single range

Environmental Protection:

Dustproof

End Application:

Aircraft e-6 tacamo

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.500 inches

Meter Body Width Behind Mounting Flange:

2.100 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0.0 to 120.0

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

1.000 inches

Features Provided:

Zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solderless lug

Special Features:

Weapon system essential

Special Markings:

Db above threshold

Material:

Steel

Surface Treatment:

Enamel lusterless

Style Designator:

Rectangular semi-flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0