NSN 6625-00-106-2576

Voltmeter - Page 1 of 2

Ac

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-106-2576

| Overall Length: |
|---|
| 3.093 inches |
| Overall Height: |
| 4.250 inches |
| Overall Width: |
| 4.625 inches |
| Frequency Rating: |
| 60.0 hertz |
| Furnished Items And Quantity: |
| Resistor 1, mtg clamps 4 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Frequency Response Range: |
| +25.000 to 125.000 hertz |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -1.0 to 1.0 at full scale single indicator all ranges |
| Unable To Decode: |
| Unable to decode or unable to decode |
| Meter Depth Behind Mounting Flange: |
| 2.156 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 4.000 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 2 bracket |
| Scale Graduation Type: |
| Nonlinear single indicator all ranges |
| Measurement Range: |

+0.0 to 300.0 volts, ac single indicator 2nd range

NSN 6625-00-106-2576 Voltmeter - Page 2 of 2



| Scale Selection Method: |
|---|
| Terminal |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud and 2 wire wrap |
| Operating Voltage Rating In Volts: |
| 115.0 ac |
| Material: |
| Plastic phenolic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set electronic equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |