NSN 6625-00-106-3033

Voltmeter - Page 1 of 2

Dc

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-106-3033

Mounting Hole Diameter:
0.156 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
3.510 inches
Mounting Bolt Circle Diameter:
3.160 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
1000.0 ohms per volt
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.030 inches
1.030 11101163
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.760 inches
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type:
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color:
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity:
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 kilovolts, dc single indicator 2nd range
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 kilovolts, dc single indicator 2nd range Movement Suspension Method:
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 kilovolts, dc single indicator 2nd range Movement Suspension Method: Jewel pivot base
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 kilovolts, dc single indicator 2nd range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 kilovolts, dc single indicator 2nd range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 kilovolts, dc single indicator 2nd range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Special Features:
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+5.0 kilovolts, dc single indicator 2nd range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 threaded stud Special Features: Also designed for nonmagnetic panel

Round flush mtg

NSN 6625-00-106-3033

Voltmeter - Page 2 of 2



Reference Number Differentiating Characteristics:

As differentiated by circuit current, measurement range, step quantity per range and panel for which designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0