

View Online at <https://aerobasegroup.com/nsn/6625-00-106-7506>

Circuit Current For Which Designed:

Dc

Overall Length:

3.500 inches

Overall Height:

0.630 inches

Overall Width:

2.500 inches

Scale Division Quantity:

25 single indicator single range

Barrel Width:

1.700 inches

Furnished Items And Quantity:

Bezel 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

3.000 inches

Meter Body Width Behind Mounting Flange:

2.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 25.0 volts, dc single indicator single range

Meter Body Height Behind Mounting Flange:

1.220 inches

Meter Barrel Depth:

1.780 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Also designed for nonmagnetic panel

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0