

View Online at https://aerobasegroup.com/nsn/6625-00-106-7524

Overall Length:

16.750 inches

Wattage Rating In Watts:

35.0

Overall Height:

3.469 inches

Overall Width:

11.250 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Electrical Connection Type:

Bnc

Internal Battery Accommodation:

Not included

Voltage Rating:

Between 115.0 volts and 230.0 volts

Output Frequency Rating:

1.0 megahertz

Electrical Connection Quantity:

2

Mounting Method:

Bench

Measurement Type:

Frequency and period average and ratio

Frequency Range:

+0.000/+10.000 megahertz multiple period and +0.001 to 2.000 megahertz multiple period and +0.000 to 10.000 megahertz multiple period and +0.000/+2.000 megahertz multiple period

Accuracy Rating:

Porm 1 count, porm time base; porm 1 count, porm time base error, porm trigger error; porm 1 count of f1, porm trigger error of f2

Gate Time:

Between 0.000001 seconds and 100.000000 seconds

Sensitivity Rating:

F1 same as input amplifier, f2 1v rms sine wave into 1000 ohms

Ratio Display:

F1 times mn/f2, time mode f2 times n/f1 times m

Period Range:

+1.0/+100000.0

Period Range Step Quantity:

5 decade steps

Count Rate:

1.0 hertz single period and 10000000.0 hertz single period



Internal Calibration Feature: Included **Display Type:** Numeric readout tube **Display Digit Quantity:** 5 **Display Units Indicator:** Not included **Display Positioned Decimal Point:** Not provided **Display Storage Facility:** Included **Remote Control Provisions:** Included Solid State Feature: Included **Inclosure Material And Location:** Aluminum case **Inclosure Surface Treatment And Location:** Enamel case **Plug-in Units Provision:** Not included **Standard Frequency Output Feature:** Included Frequency Accuracy/stability: 5 parts per 10, 000, 000 per month **Output Frequency Waveform:** Sine wave **Frequency Output Amplitude:** 3.0 volts peak to peak Phase: Single Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: T297-a