

View Online at <https://aerobasegroup.com/nsn/6625-00-106-9659>

Circuit Current For Which Designed:

Dc

Overall Length:

2.031 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

4.437 inches

Overall Width:

5.812 inches

Mounting Stud Length:

0.312 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

2.594 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-8.0 to 2.0 decibels single indicator 1st range

Mounting Stud Diameter:

0.125 inches

Scale Selection Method:

Terminal

Features Provided:

External shunting and mirror scale and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0