

View Online at <https://aerobasegroup.com/nsn/6625-00-107-2090>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.519 inches

**Mounting Hole Diameter:**

0.151 inches

**Scale Division Quantity:**

60 single indicator all ranges

**Overall Diameter:**

4.578 inches

**Mounting Bolt Circle Diameter:**

4.119 inches

**Furnished Items And Quantity:**

Nut 10; washer 14

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Six hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Panel For Which Designed:**

Nonmagnetic

**Meter Depth Behind Mounting Flange:**

2.098 inches

**Meter Body Diameter Behind Mounting Flange:**

3.640 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

6 screw and 6 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0 to 3.0 milliamperes, dc single indicator 2nd range

**Circuit Construction Type:**

Nonelectronic

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

4 threaded stud

**Special Markings:**

15 ma by upper left circuit attachment stud; 3 ma by upper right stud; 800 ua by lower left; com by lower right; plus sign by positive terminal; sealed do not open on back of meter

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Cadmium

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0