

View Online at <https://aerobasegroup.com/nsn/6625-00-107-2090>

Circuit Current For Which Designed:

Dc

Overall Length:

2.519 inches

Mounting Hole Diameter:

0.151 inches

Scale Division Quantity:

60 single indicator all ranges

Overall Diameter:

4.578 inches

Mounting Bolt Circle Diameter:

4.119 inches

Furnished Items And Quantity:

Nut 10; washer 14

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Panel For Which Designed:

Nonmagnetic

Meter Depth Behind Mounting Flange:

2.098 inches

Meter Body Diameter Behind Mounting Flange:

3.640 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

6 screw and 6 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 3.0 milliamperes, dc single indicator 2nd range

Circuit Construction Type:

Nonelectronic

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

4 threaded stud

Special Markings:

15 ma by upper left circuit attachment stud; 3 ma by upper right stud; 800 ua by lower left; com by lower right; plus sign by positive terminal; sealed do not open on back of meter

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0