NSN 6625-00-110-5229

Null Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-110-5229

| Circuit Current For Which Designed: |
|--|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 3000.0 |
| Overall Length: |
| 2.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.562 inches |
| Overall Height: |
| 4.250 inches |
| Overall Width: |
| 4.687 inches |
| Mounting Stud Length: |
| 0.500 inches |
| Environmental Protection: |
| Dustproof |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| installation besign. |
| Panel |
| - |
| Panel |
| Panel Mounting Arrangement Style: |
| Panel Mounting Arrangement Style: Four hole/stud rectangular/square |
| Panel Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: |
| Panel Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range |
| Panel Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: |
| Panel Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range |
| Panel Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: |
| Panel Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: 3.031 inches |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: 3.031 inches Movement Type: |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: 3.031 inches Movement Type: Moving coil, permanent magnet |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: 3.031 inches Movement Type: Moving coil, permanent magnet Background Color: |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: 3.031 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: 3.031 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: |
| Mounting Arrangement Style: Four hole/stud rectangular/square Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0 to 2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.000 inches Meter Body Diameter Behind Mounting Flange: 3.031 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range |

4 threaded stud

NSN 6625-00-110-5229

Null Meter - Page 2 of 2



| Scale Graduation Type: |
|--|
| Nonlinear single indicator single range |
| Mounting Stud Diameter: |
| 0.190 inches |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |