

View Online at <https://aerobasegroup.com/nsn/6625-00-110-9437>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.562 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.093 inches

Overall Width:

3.250 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.750 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 8; lockwasher 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Panel For Which Designed:

Magnetic

Meter Depth Behind Mounting Flange:

1.156 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0; 50; 100; 150; 200; percent of normal

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0