

View Online at <https://aerobasegroup.com/nsn/6625-00-111-0861>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.040 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.560 inches

**Overall Height:**

4.200 inches

**Overall Width:**

4.660 inches

**Scale Division Quantity:**

50 single indicator 2nd range

**Mounting Stud Length:**

0.625 inches

**Furnished Items And Quantity:**

Nut 2; washer 6

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-5.0 to 5.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

0.940 inches

**Meter Body Diameter Behind Mounting Flange:**

2.690 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black and red single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator 1st range

**Measurement Range:**

-20.0 to 2.0 decibels single indicator 1st range

**Mounting Stud Diameter:**

0.138 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Knife edge pointer and zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Vertical mounting

**Special Markings:**

Front of scale under volts: 600 ohm only

**Material:**

Aluminum or steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

100 ohms internal res

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0