NSN 6625-00-111-3972

Ammeter - Page 1 of 2

Dc

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-111-3972

Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
100 single indicator single range
Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.160 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
2.800 inches Movement Type:
Movement Type:
Movement Type: Moving coil, permanent magnet
Movement Type: Moving coil, permanent magnet Background Color:
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity:
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range Movement Suspension Method:
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug Style Designator:
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug Style Designator: Round flush mtg
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+2.0 amperes, dc single indicator single range Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug Style Designator: Round flush mtg Shelf Life:

NSN 6625-00-111-3972

Ammeter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A310a0