

View Online at <https://aerobasegroup.com/nsn/6625-00-113-1242>

Overall Length:

20.000 inches

Overall Height:

7.000 inches

Overall Width:

19.000 inches

Basic Shape Style:

Rectangular or square

Identification Designator:

Sg816u-80058

Installation Design:

Mechanical

Pulse Duration Per Channel:

50.000 nanoseconds output channel err-100

Pulse Rise Time Per Channel:

17.000 nanoseconds output channel err-100

Pulse Decay Time Per Channel:

17.000 nanoseconds output channel err-100

Polarity Per Channel:

Positive output channel err-100

Pulse Repetition Rate Per Channel:

10.000 pulses per second output channel err-100

Pulse Peak Amplitude Per Channel:

100.000 volts output channel err-100

Signal Data Type Per Channel:

Output channel pulse

Output Wave Shape:

Rectangular

Operating Ac Frequency In Hertz:

60.0 single voltage

External Ac Operating Voltage In Volts:

125.0 single voltage

Phase:

Single

Functional Classification:

Bb-1.1

Special Features:

50 and 18000 ohms impedance output

Functional Description:

Provides continuous rise & fall pulses w/ outputs variable over a broad range; may be synchronized by an externally applied signal; intended for intermediate & depot levels of maintenance

Entry Date:

78-09-01

Reference Data And Literature:

Handbook of operating & maintenance instructions 0969-125-0200; instrument calibration procedures navaer 17-20ag-162

Fsc Application Data:

Test set, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200