NSN 6625-00-113-3079

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-113-3079

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

4.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.390 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.390 inches

Overall Height:

4.312 inches

Overall Width:

4.312 inches

Mounting Hole Diameter:

0.250 inches

Scale Division Quantity:

60 single indicator single range

Frequency Rating:

60.0 hertz

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 6; lockwasher 6; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

300.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.937 inches

Meter Body Diameter Behind Mounting Flange:

3.875 inches

Movement Type:

Moving coil, permanent magnet

NSN 6625-00-113-3079

Voltmeter - Page 2 of 2

A310a0



Background Color: White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 screw and 4 unthreaded hole Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0 to 300.0 volts, ac single indicator single range **Scale Selection Method:** Terminal **Features Provided:** Magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized **Special Markings:** On back, made in usa Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Plastic **Special Test Features:** Complies with mil-m-10304 Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: