NSN 6625-00-113-3459

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-113-3459

| 20 |
|---|
| Overall Length: |
| 2.080 inches |
| Mounting Hole Diameter: |
| 0.120 inches |
| Scale Division Quantity: |
| 10 single indicator single range |
| Overall Diameter: |
| 2.690 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Furnished Items And Quantity: |
| Nut 2 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Panel For Which Designed: |
| Magnetic |
| Meter Depth Behind Mounting Flange: |
| 1.380 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.200 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |

Linear single indicator single range

NSN 6625-00-113-3459

Ammeter - Page 2 of 2

No Fiig: A310a0



| Measurement Range: |
|--|
| -1.0 to 1.0 milliamperes, ac single indicator single range |
| Circuit Construction Type: |
| Nonelectronic |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Material: |
| Plastic phenolic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |